

Tooling Equipment Elbows

Date: 23.04.2018



Dimensions following EN10253						processable materials
DN	Ø	Radius (max. thickness in mm)				
		Type 2D (R=1D)	Type 3D (R=1,5D)	Type 5D (R=2,5D)	R=D+100	
100	114,3	-	152 (6)	-	-	stainless steel (incl. duplex- und superduplex-steel) aluminum and aluminum-alloys copper und copper-alloys nickel und nickel-alloys titanium und titanium-alloys
125	139,7	-	190 (4)	330 (5)	-	
150	168,3	-	229 (8)	390 (8)	-	
200	219,1	-	305 (10)	510 (12)	-	
250	273	-	381 (6)	650 (12)	-	
300	323,9	324 (15)	457 (15)	775 (12)	-	
350	355,6	-	533 (15)	-	450 (6)	
400	406,4	406 (15)	610 (12)	-	506 (12)	
450	457	-	686 (15)	-	-	
500	508	508 (12)	762 (15)	-	608 (10)	
600	610	610 (15)	914 (12)	-	710 (10)	
700	711	-	1067 (12)	-	-	
800	813	-	1219 (10)	-	-	
Special Dimensions						
	Ø	Radius (max. thickness in mm)				
		Type 2D (R=1D)	Type 3D (R=1,5D)	Type 5D (R=2,5D)	R=D+100	
	100	100 (3)	150 (3)	300 (3)	-	
	123	120 (2)	180 (3)	-	-	
	129	125 (3)	187,5 (4)	312,5 (3)	-	
	150	150 (4)	229 (4)	390 (4)	-	
	200	200 (4)	300 (4)	500 (4)	-	
	250	-	375 (6)	-	350 (8)	
	300	300 (2)	450 (6)	-	400 (5)	
	368	-	533 (15)	-	-	
	419	-	610 (12)	-	519 (12)	